

## Data Sheet

### Specification

- Available in 3000mm (55 per box) and 4000mm (70 per box) variants
- From 1134mm<sup>2</sup> to 2500mm<sup>2</sup> equivalent area
- Made from UV stable ASA
- Snap on screw cover caps
- Multi Position Vent
- Available in colour: White, Mahogany, Golden Oak, Anthracite Grey, Cream, Mixed Colour Combination On Request.
- Tested to BSEN 1026:2000 & BSEND1027:2000

2000 EA 1134 mm<sup>2</sup>  
 3000 EA 1692 mm<sup>2</sup>  
 4000 EA 2500 mm<sup>2</sup>

### Performance

BS EN 1026:2000 Air Permeability

Window vent	@50Pa(m <sup>3</sup> /hr)	@50Pa(l/s)
3000L	5	1.3
4000L	4	1.1
2000L	3.25	1.17

BS EN 1027:2000 Watertightness

Window vent	Pressure at no leakage (Pa)	Classification
3000L	475	E4
4000L	600	E4
2000L	425	E4

BS EN ISO 717-1: 1997 Airborne Sound Insulation (dB)

Window vent	Dn,e,w (dB) Open
3000L	37
4000L	33
2000L	31.45

Dekko's Window System  
Kurt Greatrex



Tried and tested by leading North West fabricator Dekko Window Systems, the vent is now operational on several thousand Dekko Windows.

Dekko's Sales Director Kurt Greatrex adds, "The EasyVent is extremely simple to fit and operate, and is made from the highest UV-resistant material delivering complete peace of mind for suppliers and customers alike."

